

Specifications

Display 7" TFT LCD (capacitive touchscreen)

Screen resolution 800 x 480

Built-in camera

PoE and + 12 V DC (PSU not included) Power

Power consumption 6 W, standby 2.5 W

Dimensions 195 x 127 x 27 mm Colors Black / Gray

Plastic Body

Installation Type Wall mount Mounting options Horizontal and vertical

Possibilities of connection

Number of individual

panels

Number of multiapartment panels

Connection of additional

Up to 9 panels

monitors

Memory function Interface

Number of IP cameras

Up to 9 panels

Up to 8 monitors

Record photo into internal memory (64 photo) Multi-language graphical and WEB interface Up to 8 cameras

Main features



7" TFT touch screen



Linux hardware



Alarm connection



Connecting 8 cameras



Concierge calling



Receiving information messages





Horizontal and vertical arrangement



Alarm button with security alert



Quick control button



Calling the lift to the floor



Link app support



SIP 2.0

Functional capabilities

Intercom type Audio Intercom (no built-in camera)

Support of receiving messages Y

Yes

Select the type of screensaver

in standby mode

Single IP camera live viewing

Do Not Disturb

Yes, customizable by time
Silent mode


Yes

Software update From the web interface

From BAS-IP updates server

Color variations





Appearance and mechanical mounting

